

## 01x MXC PLUG - 01x MXC PLUG 64F OM3 RIBBON

### Basic characteristics

- ▲ Hermaphroditic PRIZM MT ferule
- ▲ Debris insensitivity of MXC plug connector



### Benefits

- ▲ High density parallel connector
- ▲ Debris insensitivity of MXC plug connector

### Applications

- ▲ Supercomputing
- ▲ Data Networking
- ▲ SAN

### Temperature range

Controlled environment (-10°C/+60°C)

### Cable parameters

Jacket material	N/A	
Cable construction	Bare ribbon	
Outer diameter	approx. 4,15mm x 0,31mm	
Fiber count	4x16	
Fiber type	MMF OM3	
Temperature range	operation:	-20°C to +70°C
	storage:	-20°C to +55°C
	installation:	-20°C to +55°C

## 01x MXC PLUG - 01x MXC PLUG 64F OM3 RIBBON

### Connector parameters

	<b>MXC</b>
Compliance	US CONEC standard
Colour of housing	Aqua
Colour of boot	Black
Polish	N/A
Insertion Loss (@850nm)	<1,2dB
Return Loss (@850nm)	>20dB

### Identification

Marking sleeve with unique serial number.

### Packaging

Each assembly in sealed PE bag, bulk pack in cardboard box.

MXC and PRIZM MT is a registered trademark of US Conec, Ltd.

\* Specifications are subject to change without notice

For more information contact our sales team at [sales@sylex.sk](mailto:sales@sylex.sk)