



FIBER TYPE	COLOUR OF FIBER
OS2	YELLOW
OM3	AQUA
OM4	MAGENTA

NOTES :

- 1 - DUST CAPS ARE INCLUDED, BUT NOT SHOWN
- 2 - CUMULATIVE TEST REPORT SYX-CTRT-01 OF MEASURED IL AND RL VALUES SENT ON DEMAND IN ELECTRONIC FORM
- 3 - OM3, OM4 - IL<0.25dB, 850nm & 1300nm
OS2 - IL<0.25dB, APC - RL>60dB, 1310nm & 1550nm
UPC - RL>50dB, 1310nm & 1550nm
- 4 - VISUAL ASPECT CHECK ACCORDING TO IEC 61300-3-35.
END FACE GEOMETRY ACCORDING TO TELCORDIA GR-326
- 5 - PRODUCT PACKED IN SEALED PE BAG, BULK PACK IN OUTER CARDBOARD BOX.
- 6 - SYLEX-SX-O LABEL ON PRODUCT PACKAGING AND OUTER CARDBOARD BOX

BOM		
NO:	DESCRIPTION	QTY
1.	CONNECTOR	1
2.	CABLE	L
3.	TRACEABILITY LABEL	1

TRACEABILITY LABEL (POS. 7)

SERIAL NUMBER
L = XXm
MM/YYYY

REVISION-DATE: A - 07.10.2003	CHANGE:	DRAWN BY, DATE: M. Golias 2003/10/07	TITLE: <h1>PIGTAIL</h1>		
- zalozeny nový vykres		CHECKED BY, DATE: M. Kadlec 2003/10/07			
REVISION-DATE: B - 05.11.2015	CHANGE:	APPROVED BY, DATE: M. Huserikova 2003/10/07	PRODUCT SPECIFICATION:	DIMENSIONS IN MM UNLESS SPECIFIED	SCALE: NO SCALE
- zmena optických parametrov			PRODUCT NUMBER: X-XXX-XXX-XXX-XXX/XX/XXXX	DRAWING NUMBER: 1-S-2990_1_B	SHEET NO. 1 of 1
REVISION-DATE: X - DD.MM.YYYY	CHANGE:		B	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SYLEX s.r.o AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	
XXX					SIZE A3