

1x24f MTP to 24xLC 900um 24-fiber direct split

Basic characteristic

- ▲ Fan-out legs protected 900um transparent tubing
- ▲ Female/male type of MTP® connector



Applications

- ▲ Plug & Play modules

Temperature range

Indoor controlled environment (-10°C/+60°C)

Cable parameters

Jacket material	Nylon	
Cable construction	Bare fibers	
Outer diameter	0,9mm	
Fiber count	24	
Fiber type	SM OS2 or MMF OM3/OM4/OM5	
Temperature range	operation:	-10°C to +70°C
	storage:	-25°C to +70°C
	installation:	-5°C to +50°C

1x24f MTP to 24xLC 900um 24-fiber direct split

Connector parameters

	MTP®/MTP® PRO SM/MM	LC SM/LC MM
Compliance	US CONEC standard	Telcordia GR-326
Colour of connector	Green (APC) Aqua/Magenta/Lime Green	Blue/Green (APC) Aqua/Magenta/Lime Green
Colour of boot	Black	Green (APC) White
Polish	Angled (APC) Flat	Angled (APC) Flat
Insertion Loss (acc. IEC 61300-3-4 method B)	<0,35dB (@1310/1550nm / (@850/1300nm)	<0,25dB (@1310/1550nm / (@850/1300nm)
Return Loss (acc. IEC 61300-3-6)	>50dB(APC) / >20dB (@1310/1550nm / (@850/1300nm)	>50dB(UPC)/>60dB(APC) / >30dB (@1310/1550nm / (@850/1300nm)

Identification

Traceability label with unique serial number only on one side

Packaging

Each assembly in plastic bag, bulk pack in cardboard box.

MTP is a registered trademark of US Conec, Ltd.
* Specifications are subject to change without notice

For more information contact our sales team at sales@sylex.sk