

Fully loaded ODF

Basic characteristics

- ▲ Width 19"
- ▲ Height 1U / 2U
- ▲ Space for 2 back plates
- ▲ Two elements for Kevlar fixation



Benefits

- ▲ Exchangeable front panels and back plates
- ▲ Adjustable depth of position in rack

Capacity

- ▲ SC simplex/duplex cut out
 - 12, 24 ports (1U)
 - 48, 72 ports (only simplex) (2U)
- ▲ ST, FC simplex cut out
 - 12, 24 ports (1U)
 - 48, 72 ports (2U)

Temperature range

Controlled temperature (-10°C /+60°C)

Parameters

Dimensions	482 x 251x 44 mm (1U) 482 x 251x 88 mm (2U)
Material	powdered coating steel
Colour	light gray RAL7035 (1U/2U) deep black RAL9005 (1U)
Capacity	12 – 144 fibers/connectors
Cable entry port	2x PG13,5 (1U) 4x PG13,5 (2U)
Optical performance	IL<0,25dB, RL>50dB (UPC), >60(APC), >25(MM) <i>details in section pigtails</i>

Identification

Label with unique serial number.

Packaging

Each patchpanel in cardboard box, bulk pack on palette.

* Specifications are subject to change without notice

For more information contact our sales team at sales@sylex.sk