

MTP CXP/CFP to MTP QSFP fanout

Basic characteristics

- ▲ Complete fiber optic interconnection links for active devices
- ▲ 3x40Gbit parallel transmission over 1 cable
- ▲ Laser optimised MM bend insensitive fiber
- ▲ MTP[®] PRO connector optional



Temperature range	Controlled environment (-10°C/+60°C)
-------------------	--------------------------------------

Cable parameters		
Jacket material	LSZH	
Cable construction	Round cable	
Outer diameter	3,8mm	
Fiber count	24	
Fiber type	MMF OM3/OM4	
Temperature range	operation:	-10°C to +70°C
	storage:	-25°C to +70°C
	installation:	-5°C to +50°C

Connector parameters	24F MTP	12F MTP [®] /MTP [®] PRO
Compliance	US CONEC standard	US CONEC standard
Colour of housing	Aqua/Magenta	Aqua/Magenta
Colour of boot	Black	Black
Polish	Flat (PC)	Flat (PC)
Insertion Loss	<0,35dB	<0,35dB
Return Loss	>20dB	>20dB

Identification
Traceability label with unique serial number on both ends of cable assembly.

Packaging
Each assembly in sealed PE bag, bulk pack in cardboard box.
Longer lengths coiled on cardboard reel.

MTP is a registered trademark of US Conec, Ltd.
* Specifications are subject to change without notice

y

For more information contact our sales team at sales@sylex.sk