

TP-01 Temperature probe sensor

Basic characteristic

- ▲ TP-01 is small form factor temperature probe.
- ▲ TP-01 has small dimensions.



Benefits

- ▲ Small a flexible cable.
- ▲ Direct mountable.

Applications

- ▲ Temperature measurement.
- ▲ Temperature compensation of strain sensors.

Performance properties

Temperature range	-20°C up to +110°C
Temperature accuracy (guaranteed) ¹⁾	<1°C
Temperature accuracy (typical) ¹⁾	<1°C
Temperature precision (guaranteed) ²⁾	±0,3°C
Temperature precision (typical) ²⁾	±0,2°C
Ingress Protection rating	IP 67

¹⁾ Accuracy is established for each individual sensor under laboratory conditions and it includes hysteresis, non-linearity and repeatability of the sensor.

²⁾ Precision is established on a batch basis and it includes hysteresis, non-linearity, repeatability and reproducibility of the sensor.

TP-01 Temperature probe sensor

Physical properties

Housing material	Stainless steel SS316L
Dimensions (without cable) ¹⁾	Ø5 mm x 58 mm
Weight (without cable)	25g
Cable type	900µm PVDF tubing (yellow)
Cable length ²⁾	1mtr
Cable Bend Radius (dynamic)	30mm
Cable Bend Radius (static)	15mm
Connector type ³⁾	FC/APC
Mounting method	Surface mounting

¹⁾ For further dimensions details see the product drawing

²⁾ Cable length is extendable on request

³⁾ Other connector types available on request

Packaging

Cardboard box with dimensions: 370x290x45mm

Quality statement

TP-01 sensor is compliant with IEC 61757:2018
 All sensors are 100% tested and calibrated at SYLEX
 Sensor is manufactured according to ISO 9001:2008 and ISO 14001:2004

Optional accessories

- ▲ **LCP-01 Longer cable pigtails** – used to extend the cable lengths from 1mtr up to 20mtr.

For more information contact our sales team at sales@sylex.sk

* Specifications are subject to change without notice