

LC-LC 24-fiber Duralino Miniflex trunk - Uniboot

Basic characteristics

- ▲ Durable material
- ▲ Compact
- ▲ Light weight



Benefits

- ▲ Miniflex cable – outer diameter 4,0mm
- ▲ Durable metal fan-out

Applications

- ▲ DataCenter cabling
- ▲ Inside building interconnections
- ▲ Direct patching of ODFs

Temperature range

Controlled environment (-10°C/+60°C)

Cable parameters

Jacket material	LSZH	
Cable construction	Miniflex cable	
Outer diameter	4,0mm	
Fiber count	24	
Fiber type	SM OS2 or MMF OM3/OM4	
Temperature range	operation:	-20°C to +85°C
	installation:	-20°C to +60°C

LC-LC 24-fiber Duralino Miniflex trunk - Uniboot

Connector parameters

	LC SM	LC MM
Compliance	Telcordia GR-326	Telcordia GR-326
Color of housing	Blue (UPC)/Green (APC)	Aqua/Magenta/Lime Green
Color of boot	White (UPC) or Green (APC)	White
Polish	Flat (UPC) or Angled (APC)	Flat (PC)
Insertion Loss (acc. IEC 61300-3-4 method B)	<0,25dB (@1310/1550nm)	<0,25dB (@850/1300nm)
Return Loss (acc. IEC 61300-3-6)	>50dB (UPC)/>60dB (APC) (@1310/1550nm)	>30dB (@850/1300nm)

Identification

Traceability label with unique serial number on both ends of cable assembly.

Packaging

Each assembly in plastic bag, bulk pack in cardboard box.
Longer lengths coiled on cardboard/wooden reel.

* Specifications are subject to change without notice

For more information contact our sales team at sales@sylex.sk