



## NOTES :

- 1 - DUST CAPS ARE INCLUDED, BUT NOT SHOWN
- 2 - CUMULATIVE TEST REPORT OF MEASURED IL AND RL VALUES SENT ON DEMAND IN ELECTRONIC FORM
- 3 - OM3, OM4, OM5 - IL<0.25dB , RL>30dB , 850nm & 1300nm  
OS2 - IL<0.25dB, LC/APC - RL>60dB, 1310nm & 1550nm  
LC/UPC - RL>50dB, 1310nm & 1550nm  
IL CONNECTOR VALUE ACCORDING IEC 61300-3-4 method B  
RL CONNECTOR VALUE ACCORDING IEC 61300-3-6
- 4 - VISUAL ASPECT CHECK ACCORDING TO IEC 61300-3-35.  
END FACE GEOMETRY ACCORDING TO TELCORDIA GR-326
- 5 - ASSEMBLY PACKED IN SEALED PE BAG,  
BULK PACK IN OUTER CARDBOARD BOX
- 6 - CABLE LENGTH TOLERANCES AND FANOUT LENGTH TOLERANCES  
ACCORDING TO SYLEX STANDARD [1-S-8000](#)
- 7 - TRACEBILITY LABEL ON THE CABLE CONTAINS SERIAL NUMBER,  
DATE OF PRODUCTION AND ASSEMBLY LENGTH
- 8 - CROSS AND STRAIGHT CONNECTION ACCORDING TO SYLEX STANDARD [1-S-7307](#)

## ORDERING CODE

C2XX-XXX-XXX-X

	S STRAIGHT, LEAVE EMPTY FOR CROSS
	xxx cable length [050 = 50m, 001 = 1m]
	1 SIMPLEX CONNECTOR, 2 DUPLEX CONNECTOR, U UNIBOOT CONNECTOR
	L LC/UPC, A LC/APC *
	L LC/UPC, A LC/APC *
	9 OS2, 3 OM3, 4 OM4, 5 OM5
	2 1.8mm, 3 2.8mm **
	2 DUPLEX
	C Cord

\* OTHER CONNECTOR TYPES ON REQUEST  
\*\* OTHER CABLE TYPES ON REQUEST

REVISION-DATE: A - 28.10.2019	CHANGE:	DRAWN BY, DATE: P. Gašpár 2019/10/28	TITLE: <b>2f Duplex Jumper</b>		
New drawing		CHECKED BY, DATE: Pavlov/Matúš			
REVISION-DATE:	CHANGE:	APPROVED BY, DATE: I.Brestovanská	PRODUCT SPECIFICATION: -	DIMENSIONS IN MM UNLESS SPECIFIED	SCALE: NO SCALE
REVISION-DATE: X - DD.MM.YYYY	CHANGE:	PRODUCT NUMBER: C2XX-XX2-xxx	DRAWING NUMBER: 1-S-7402_1_A	SHEET NO. 1 of 1	
A			THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SYLEX s.r.o AND ANY USE WITHOUT PRIOR WRITTEN PERMISSION IS PROHIBITED		
			SIZE A3		