


## 01x MXC - 12x LC PC 2,0mm 12F ROUND FANOUT

### Basic characteristics

- ▲ Compact and small footprint receptacle on card-edge
- ▲ Debris insensitivity of back-plane connection



### Benefits

- ▲ High density card-edge interface
- ▲ Low profile design

### Applications

- ▲ High-speed computing
- ▲ Testing of individual fiber optic channels

### Temperature range

Indoor controlled environment (-10°C/+60°C)

### Cable parameters

Jacket material	LSZH	
Cable construction	Round cable	
Outer diameter	3,0mm	
Fiber count	16	
Fiber type	MMF OM3/OM4	
Temperature range	operation:	-20°C to +70°C
	storage:	-40°C to +70°C
	installation:	0°C to +70°C



01x MXC - 12x LC PC 2,0mm 12F ROUND FANOUT

**Connector parameters**

	<b>MXC</b>	<b>LC MM</b>
Compliance	US CONEC standard	Telcordia GR-326
Colour of housing	Aqua	Aqua/Magenta
Colour of boot	Black	White
Polish	N/A	Flat (PC)
Insertion Loss (acc. IEC 61300-3-4 method B)	<0,6dB (@850nm)	<0,25dB (@850nm)
Return Loss (acc. IEC 61300-3-6)	>25dB (@850nm)	>30dB (@850nm)

**Identification**

Marking sleeve with unique serial number.

**Packaging**

Each assembly in sealed PE bag, bulk pack in cardboard box.

MXC is a registered trademark of US Conec, Ltd.  
\* Specifications are subject to change without notice

For more information contact our sales team at [sales@sylex.sk](mailto:sales@sylex.sk)