

## PRIZM LT - PRIZM LT 12F round jumper

### Basic characteristics

- ▲ Simple assembly into Avago modules
- ▲ Miniature detachable connector for high speed optical interconnection
- ▲ The PRIZM LT connector consists of a multi-fiber ferrule with a photonic turn TIR (total internal reflection) lens array



### Benefits

- ▲ Optimizes air-flow
- ▲ High I/O density directly on a PCB
- ▲ Low profile design
- ▲ Provides excellent coupling to high bandwidth mini-parallel optic modules

### Applications

- ▲ Telecommunications
  - Servers
- ▲ Data Networking
  - Data communication centers
  - High-speed computer applications

### Temperature range

Indoor controlled environment (-10°C/+60°C)

### Cable parameters

Jacket material	OFNG-LS	
Cable construction	Round cable	
Outer diameter	1,8mm	
Fiber count	12	
Fiber type	MMF OM3 / OM4	
Temperature range	operation:	0°C to +70°C
	storage:	-20°C to +70°C
	installation:	0°C to +70°C

## PRIZM LT - PRIZM LT 12F round jumper

### Connector parameters

	PRIZM LT
Compliance	US CONEC standard
Colour of housing	Black
Colour of boot	Black
Polish	N/A
Insertion Loss (acc. IEC 61300-3-4 method B)	<2,1dB (@850nm)

### Identification

Traceability label with unique serial number on both ends of cable assembly.

### Packaging

Each assembly in sealed PE bag, bulk pack in cardboard box.

PRIZM LT is a registered trademark of US Conec, Ltd.  
\* Specifications are subject to change without notice

For more information contact our sales team at [sales@sylex.sk](mailto:sales@sylex.sk)