


## 4x SN - 4x SN 8-fiber Duralino fanout - Simplex

### Basic characteristics

- ▲ Constructed of high-quality fiber optic cable and components
- ▲ Two fibers connection for SFP-DD and QSFP-DD
- ▲ With push-pull boot for easy insertion/extraction
- ▲ Very small form factor duplex connector
- ▲ Fan-out legs are protected by 1,6mm simplex tubing with Aramid yarns
- ▲ 3 times higher density than LC duplex connector



### Applications

- ▲ Data center
- ▲ Storage Area Network
- ▲ Short distance connections within a single rack or cabinet

### Temperature range

Indoor controlled environment (-10°C/+60°C)

### Cable parameters

Jacket material	LSZH	
Cable construction	Round single jacket cable	
Outer diameter	3.0mm	
Fiber count	12	
Fiber type	SMF OS2 MMF OM3/OM4/OM5	
Temperature range	operation:	-10°C to +70°C
	storage:	-25°C to +70°C
	installation:	-5°C to +50°C
CPR	C <sub>ca</sub> -s1a, d1, a1	

### Connector parameters

	<b>SN SM/MM</b>
Compliance	Telcordia GR-326
Color of housing	Blue (UPC) Aqua / Magenta / Lime Green
Color of boot	White (T-boot)
Polish	Flat SM (UPC) Flat MM (PC)
Insertion Loss (acc. IEC 61300-3-4 method B)	<0,25dB (@1310/1550nm/@850/1300nm)
Return Loss (acc. IEC 61300-3-6)	>50dB(UPC) / >20dB (@1310/1550nm/@850/1300nm)

## 4x SN - 4x SN 8-fiber Duralino fanout - Simplex

---

### Identification

---

Traceability label with unique serial number on both ends of cable assembly.

---

### Packaging

---

Each assembly in sealed PE bag, bulk pack in cardboard box. Longer lengths coiled on cardboard/wooden reel.

---

\*Specifications are subject to change without notice

**For more information contact our sales team at [sales@sylex.sk](mailto:sales@sylex.sk)**