

SN BTW – SN BTW 2-fiber Duplex jumper

Basic characteristics

- ▲ Constructed of high-quality fiber optic cable and components
- ▲ Two fibers connection for SFP-DD and QSFP-DD
- ▲ Very small form factor duplex connector

Applications

- ▲ Data center
- ▲ Storage Area Network



Temperature range

Indoor controlled environment (-10°C/+60°C)

Cable parameters

Jacket material	LSZH	
Cable construction	Buffered fiber	
Outer diameter	0.9mm	
Fiber count	2	
Fiber type	SMF OS2 MMF OM3/OM4/OM5	
Temperature range	operation:	-10°C to +70°C
	storage:	-25°C to +70°C
	installation:	-5°C to +50°C

Connector parameters

	SN BTW1	SM/MM
Compliance	Telcordia GR-326	
Color of housing	Blue (UPC)	
Color of boot	Aqua / Magenta / Lime Green	
Polish	White	
Insertion Loss (acc. IEC 61300-3-4 method B)	Flat SM (UPC) Flat MM (PC)	
Return Loss (acc. IEC 61300-3-6)	<0,25dB >50dB(UPC) / >20dB (@1310/1550nm/@850/1300nm)	

Identification

Traceability label with unique serial number.

Packaging

Each assembly in sealed PE bag, bulk pack in cardboard box.

*Specifications are subject to change without notice

*Cable with PVC outer jacketed material available on demand

For more information contact our sales team at sales@sylex.sk