



ORDERING CODE

SSSX-xxU-xxx-X

- S STRAIGHT, LEAVE EMPTY FOR CROSS
 - xxx cable length [050 = 50m, 001 = 1m] *
 - U Uniboot connector
 - AA LC/APC-LC/APC, LL LC/PC-LC/PC *
 - 9 OS2, 3 OM3, 4 OM4, 5 OM5
 - S SPECIAL PRODUCTS
- * OTHER CONNECTOR TYPES ON REQUEST
 ** Typical lengths up to 5 meters. Other versions upon prior consultation.

NOTES :

- 1 - DUST CAPS ARE INCLUDED, BUT NOT SHOWN
- 2 - CUMULATIVE TEST REPORT OF MEASURED IL AND RL VALUES SENT ON DEMAND IN ELECTRONIC FORM
- 3 - OM3, OM4, OM5 - IL<0.25dB , RL>30dB , 850nm & 1300nm
 OS2 - IL<0.25dB, LC/APC - RL>60dB, 1310nm & 1550nm
 LC/UPC - RL>50dB, 1310nm & 1550nm
 IL CONNECTOR VALUE ACCORDING IEC 61300-3-4 method B
 RL CONNECTOR VALUE ACCORDING IEC 61300-3-6
- 4 - VISUAL ASPECT CHECK ACCORDING TO IEC 61300-3-35.
 END FACE GEOMETRY ACCORDING TO TELCORDIA GR-326
- 5 - ASSEMBLY PACKED IN SEALED PE BAG, BULK PACK IN OUTER CARDBOARD BOX.
- 6 - CABLE LENGTH TOLERANCES ACCORDING TO SYLEX STANDARD [1-S-8000](#)
- 7 - TRACEBILITY LABEL ON THE CABLE CONTAINS SERIAL NUMBER, DATE OF PRODUCTION AND ASSEMBLY LENGTH

REVISION-DATE: A - 30.06.2021	CHANGE:	DRAWN BY, DATE: P.Gaspar 2021/06/30	TITLE: LCD Uniboot Armored Patchcord		
NEW DRAWING		CHECKED BY, DATE: L.Miskerik 2021/06/30			
REVISION-DATE:	CHANGE:	APPROVED BY, DATE: Matus/Smelh. 2021/06/30	PRODUCT SPECIFICATION: -	DIMENSIONS IN MM UNLESS SPECIFIED	SCALE: NO SCALE
REVISION-DATE:	CHANGE:	PRODUCT NUMBER: XXX-XXX-xxx-X	DRAWING NUMBER: 1-W-8602_1_A	SHEET NO. 1 of 1	
		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO SYLEX s.r.o AND ANY USE WITHOUT PRIOR WRITTEN PERMISSION IS PROHIBITED			SIZE A3